

RESIDENTIAL AND COMMERCIAL R32

.....

MULTISPLIT INTERNAL UNITS



Compact cassette 60x60 HTFU 260 ZL - HTFU 350-530 ZAL



Standard remote control with built-in temperature sensor (Follow me function)

Model			HTFU 260 ZL	HTFU 350 ZAL	HTFU 530 ZAL
Type			Indoor cassette unit		
Control (included)			Remote control		
Rated heating	Cooling	kW	2.60	3.50	5.30
	Heating	kW	2.90	4.10	5.40
Electrical data					
Power	Ph-V-Hz		-	-	-
Connection wires between I.U. and O.U.	no.		4	4	4
Refrigerant circuit					
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø12.74(1/2")
Product specifications					
Dimensions	LxDxH	mm	570x570x260	570x570x260	570x570x260
Net weight		Kg	14.5	16.2	16.2
Sound pressure level	Hi/Mi/Lo	dB(A)	38/33/29	41/37/34	44/42/41
Sound power level	Hi	dB(A)	53	58	56
Treated air (High / Med. / Low)		m ³ /h	580/500/450	617/504/415	680/560/500
Motor power (Output)		W	45	45	45
Accessories			TFP200ZA		
Decorative panel					
Optional parts					
Wi-Fi module			NO		
Wired remote control			YES		
Manual centralized control			YES ¹		
Wi-Fi centralized control			YES ¹		

1. Contact the Hokkaido Italia technical department for installation.

MULTISPLIT INTERNAL UNITS



Medium head ducted

HUCU 260 ZL - HUCU 350-530 ZAL



Standard remote control with built-in temperature sensor (Follow me function)

Model			HUCU 260 ZL	HUCU 350 ZAL	HUCU 530 ZAL
Type			Indoor duct unit		
Control (included)			Remote control		
Rated heating	Cooling	kW	2.60	3.50	5.30
	Heating	kW	2.90	3.80	5.60
Electrical data					
Power	Ph-V-Hz		-	-	-
Connection wires between I.U. and O.U.	no.		4	4	4
Refrigerant circuit					
Diameter of refrigerant piping on liquid/gas		mm (inches)	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø12.74(1/2")
Product specifications					
Dimensions	LxDxH	mm	700x450x200	700x450x200	880x674x210
Net weight		Kg	18	18	24.3
Sound pressure level	Hi/Mi/Lo	dB(A)	40/34.5/27.5	40/34.5/27.5	41.5/38/33
Sound power level	Hi	dB(A)	58	59	59
Treated air (High / Med. / Low)		m ³ /h	500/340/230	600/480/300	880/650/350
Fan pressure head	Std/Max	Pa	25/40	25/60	25/100
Motor power (Output)		W	130	130	90
Optional parts					
Wi-Fi module			NO		
Wired remote control			YES		
Manual centralized control			YES ¹		
Wi-Fi centralized control			YES ¹		

1. Contact the Hokkaido Italia technical department for installation.