

# PROJECT VRF R410A FULL DC INVERTER

.....

## HFIU XRV-P Console



The control must be purchased as an accessory



### Characteristics

- 2.20~4.50 kW** | 4 power levels
- 210 mm deep** | Ultra-compact design
- Dual capacity to control air output floor: upper and lower
- 7 fan speeds
- Front and side air intake
- Anti-formaldehyde filter** | To eliminate the harmful effects of the gases released in the environments

Model	HFIU 225 XRV-P		HFIU 285 XRV-P		HFIU 365 XRV-P		HFIU 455 XRV-P	
Control (included)	none							
Rated cooling capacity	kW		2.20		2.80		3.60	
Rated heating capacity	kW		2.60		3.20		4.00	
<b>Electrical data</b>								
Power supply	Ph-V-Hz		1-220~240V-50Hz					
Electrical absorption	W		20		25		35	
<b>Product specifications</b>								
Air flow (1)	Max~Min	m³/h	430~229		510~229		510~229	
Sound pressure level at 1 m (1)	Max~Min	dB(A)	38~26		39~27		39~27	
Sound power level (1)	Max~Min	dB(A)	54~42		55~43		55~43	
Dimensions	LxHxD	mm	700x600x210					
Net weight	Kg		14		15			
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")					
Condensate drain	Ø mm		16					
<b>Accessories</b>								
Remote control			DHIR-5-6-XRV-K-P					
Wired remote control			DHW-5-6-XRV-K-P					
<b>Optional parts</b>								
Centralised control			See on page 123					

(1) Values related to Max and Min speed of 7 levels settable by remote control.

## HFCU XRV-P Flush floor



The control must be purchased as an accessory



### Characteristics

- 2.80~5.60 kW** | 3 power levels
- 29 dB(A)** (2.80 kW) | Extremely quiet
- Lower air intake
- Built-in expansion valve and electronic control

Model	HFCU 285 XRV-P		HFCU 365 XRV-P		HFCU 565 XRV-P	
Control (included)	none					
Rated cooling capacity	kW		2.80		3.60	
Rated heating capacity	kW		3.20		4.00	
<b>Electrical data</b>						
Power supply	Ph-V-Hz		1-220~240V-50Hz			
Electrical absorption	W		45		55	
<b>Product specifications</b>						
Air flow (1)	Max~Min	m³/h	569~421		624~375	
Fan pressure head	Std/Max	Pa	10/10			
Sound pressure level at 1 m (1)	Max~Min	dB(A)	36~29		37~30	
Sound power level (1)	Max~Min	dB(A)	54~47		55~48	
Dimensions	LxHxD	mm	840x545x212		1040x545x212	
Net weight	Kg		21		25.5	
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")			
Condensate drain	Ø mm		16			
<b>Accessories</b>						
Remote control			DHIR-5-6-XRV-K-P			
Wired remote control			DHW-5-6-XRV-K-P			
<b>Optional parts</b>						
Centralised control			See on page 123			

(1) Values related to Max and Min speed of 7 levels settable by remote control.