

PROJECT VRF R410A FULL DC INVERTER

HFIU XRV-P Console



The control must be purchased as an accessory



Main features

- 4 power levels: 2.20~4.50 kW.
- Ultra-compact design: only 210 mm deep.
- Dual capacity to control air output floor: upper and lower.
- 7 fan speeds.
- Front and side air intake.
- Anti-formaldehyde filter to eliminate the harmful effects of the gases released in the environments.

Model		HFIU 225 XRV-P	HFIU 285 XRV-P	HFIU 365 XRV-P	HFIU 455 XRV-P	
Rated cooling capacity	kW	2.2	2.8	3.6	4.5	
Rated heating capacity	kW	2.6	3.2	4	5	
Electrical data						
Power supply	Ph-V-Hz	1-220~240V-50Hz				
Electrical absorption	W	20	25	25	35	
Product specifications						
Air flow (1)	Max~Min	m³/h	430~229	510~229	510~229	660~400
Sound pressure level at 1 m (1)	Max~Min	dB(A)	38~26	39~27	39~27	42~36
Sound power level (1)	Max~Min	dB(A)	54~42	55~43		58~52
Dimensions	LxHxD	mm	700x600x210			
	Net weight	Kg	14	15		
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")			
Condensate drain		Ø mm	16			
Serial control		type	none			
Accessories						
Remote control		DHIR-5-6-XRV-K-P				
Wired remote control		DHW-5-6-XRV-K-P				
Optional parts						
Centralised control		See compatibility table on p. 69				

(1) Values related to Max and Min speed of 7 levels settable by remote control.

HFCU XRV-P Flush floor



The control must be purchased as an accessory



Main features

- 3 power levels: 2.80~5.60 kW.
- Extremely quiet: only 29 dB(A) (2.80 kW).
- Lower air intake.
- Built-in expansion valve and electronic control.

Model		HFCU 285 XRV-P	HFCU 365 XRV-P	HFCU 565 XRV-P	
Rated cooling capacity	kW	2.8	3.6	5.6	
Rated heating capacity	kW	3.2	4	6.3	
Electrical data					
Power supply	Ph-V-Hz	1-220~240V-50Hz			
Electrical absorption	W	45	55	88	
Product specifications					
Air flow (1)	Max~Min	m³/h	569~421	624~375	1150~830
Fan pressure head	Std/Max	Pa	10/10		
Sound pressure level at 1 m (1)	Max~Min	dB(A)	36~29	37~30	41~31
Sound power level (1)	Max~Min	dB(A)	54~47	55~48	59~49
Dimensions	LxHxD	mm	840x545x212	1040x545x212	1340x545x212
	Net weight	Kg	21	25.5	30.5
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")		
Condensate drain		Ø mm	16		
Serial control		type	none		
Accessories					
Remote control		DHIR-5-6-XRV-K-P			
Wired remote control		DHW-5-6-XRV-K-P			
Optional parts					
Centralised control		See compatibility table on p. 69			

(1) Values related to Max and Min speed of 7 levels settable by remote control.