

# PROJECT VRF R410A FULL DC INVERTER

## Main features

## HKEU XRV-K Wall



Infrared remote control



- 6 power levels: 2.20~9.00 kW.
- Extremely quiet: only 29 dB(A) (2.20 kW)
- New built-in electronic expansion valve with 2000 pulse/min.
- Washable standard filter & anti-formaldehyde filter to eliminate the harmful effects of the gas released in the environments.

Model		HKEU 226 XRV-K	HKEU 366 XRV-K	HKEU 456 XRV-K	HKEU 566 XRV-K	HKEU 716 XRV-K	HKEU 906 XRV-K	
Rated cooling capacity	kW	2.2	3.6	4.5	5.6	7.1	9.0	
Rated heating capacity	kW	2.4	4.0	5.0	6.3	8.0	10.0	
<b>Electrical data</b>								
Power supply	Ph-V-Hz	1-220~240V-50Hz						
Electrical absorption	W	7	18	18	25	40	65	
<b>Product specifications</b>								
Air flow	L/M/H	m <sup>3</sup> /h	356/393/422	488/573/656	424/507/594	547/648/747	809/1005/1195	867/1067/1421
Sound pressure level at 1 m	L/M/H	dB(A)	29/30/31	30/32/33	31/33/35	34/36/38	36/39/44	38/43/48
Sound power level	L/M/H	dB(A)	41/42/43	42/44/45	43/45/47	46/48/50	48/51/56	50/55/60
Dimensions	LxHxD	mm	835x280x203		990x315x223		1194x343x262	
	Net weight	Kg	8.4	11.4	12.8		17	
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")			9.52 (3/8") - 15.9 (5/8")		
Condensate drain		Ø mm	16					
Serial control		type	IR Remote control					
<b>Optional parts</b>								
Wired remote control			DTW 3 IHXR TOUCH / DTW IHXR SIMPLY / DTWS 4 IHXR COMPACT					
Centralised control			See compatibility table on p. 69					

## Main features

## HSFU XRV-K Floor/ceiling



Infrared remote control



- 5 power levels: 5.60~14.00 kW.
- 3 fan speeds.
- Auto Swing function that optimizes the distribution of air flow in the environment.
- Built-in electronic expansion valve.
- Easy installation with unit attached to the wall or ceiling.
- Electric wiring and refrigerant connections can be reached from the air intake grille.

Model		HSFU 565 XRV-K	HSFU 715 XRV-K	HSFU 905 XRV-K	HSFU 1125 XRV-K	HSFU 1405 XRV-K	
Rated cooling capacity	kW	5.6	7.1	9.0	11.2	14.0	
Rated heating capacity	kW	6.3	8.0	10.0	12.5	15.5	
<b>Electrical data</b>							
Power supply	Ph-V-Hz	1-220~240V-50Hz					
Electrical absorption	W	94		126	130		
<b>Product specifications</b>							
Air flow	L/M/H	m <sup>3</sup> /h	720/830/930		1050/1170/1280		1580/1700/1890
Sound pressure level at 1 m	L/M/H	dB(A)	36/38/40		40/43/45		42/45/47
Sound power level	L/M/H	dB(A)	51/53/54		53/55/56		55/56/58
Dimensions	LxHxD	mm	990x660x203		1280x660x203		1670x680x244
	Net weight	Kg	27		33		49
Refrigerant connections	Liquid/Gas	Ø mm (inch)	9.52 (3/8") - 15.9 (5/8")				
Condensate drain		Ø mm	25				
Serial control		type	IR Remote control				
<b>Optional parts</b>							
Wired remote control			DTW 3 IHXR TOUCH / DTW IHXR SIMPLY / DTWS 4 IHXR COMPACT				
Centralised control			See compatibility table on p. 69				