

PROJECT VRF R410A FULL DC INVERTER

HTFU XRV-P Compact cassette 60x60



The control must be purchased as an accessory



Main features

- 4 power levels: 2.20-4.50 kW.
- Ultra-compact design.
- Extremely quiet: only 22 dB(A) (2.20~2.80 kW).
- 360° air diffusion.
- Condensate drain pump with possibility of raising the discharge up to 500 mm from the lower part of the unit.

Model			HTFU 225 XRV-P	HTFU 285 XRV-P	HTFU 365 XRV-P	HTFU 455 XRV-P
Rated cooling capacity	kW		2.2	2.8	3.6	4.5
Rated heating capacity	kW		2.4	3.2	4	5
Electrical data						
Power supply	Ph-V-Hz		1-220~240V-50Hz			
Electrical absorption	W		35	35	40	50
Product specifications						
Air flow (1)	Max~Min	m ³ /h	576~405		604~400	
Sound pressure level at 1.4 m (1)	Max~Min	dB(A)	35~22		41~28	
Sound power level (1)	Max~Min	dB(A)	51~38		56~43	
External dimensions	LxHxD	mm	630x260x570			
	Net weight	Kg	18		19.2	
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")			
Condensate drain		Ø mm	32			
Serial control		type	none			
Accessories						
Decorative panel			TFP 155 XRV-P			
Panel dimensions	LxHxD	mm	647x550x647			
	Net weight	Kg	2.5			
Remote control			DHIR-5-6-XRV-K-P			
Wired remote control			DHW-5-6-XRV-K-P			
Optional parts						
Centralised control			See compatibility table on p. 69			

(1) Values related to Max and Min speed of 7 levels settable by remote control.

HTBU XRV-P Cassette 84x84



The control must be purchased as an accessory



Main features

- 5 power levels: 5.60-14.00 kW.
- Low resistance and low noise fan profile.
- Condensate drain pump with possibility of raising the discharge up to 750 mm from the lower part of the unit.
- Internal electronic control.
- Pre-set for the connection of a channel for the intake of external air.

Model			HTBU 565 XRV-P	HTBU 715 XRV-P	HTBU 905 XRV-P	HTBU 1125 XRV-P	HTBU 1405 XRV-P
Rated cooling capacity	kW		5.6	7.1	9	11.2	14
Rated heating capacity	kW		6.3	8	10	12.5	16
Electrical data							
Power supply	Ph-V-Hz		1-220~240V-50Hz				
Electrical absorption	W		31	46	75	94	
Product specifications							
Air flow (1)	Max~Min	m ³ /h	1029~704	1200~748	1596~1034		1727~1224
Sound pressure level at 1.4 m (1)	Max~Min	dB(A)	43~34	45~34	47~36		50~38
Sound power level (1)	Max~Min	dB(A)	56~47	58~47	61~50		64~52
External dimensions	LxHxD	mm	840x230x840			840x300x840	
	Net weight	Kg	23.2		28.4		30.7
Refrigerant connections	Liquid/Gas	Ø mm (inch)	9.52 (3/8") - 15.9 (5/8")				
Condensate drain		Ø mm	32				
Serial control		type	none				
Accessories							
Decorative panel			TBP 712 IHXR				
Panel dimensions	LxHxD	mm	950x70x950				
	Net weight	Kg	5.8				
Remote control			DHIR-5-6-XRV-K-P				
Wired remote control			DHW-5-6-XRV-K-P				
Optional parts							
Centralised control			See compatibility table on p. 69				

(1) Values related to Max and Min speed of 7 levels settable by remote control.