

PROJECT VRF R410A FULL DC INVERTER

.....

HKEU XRV-P Wall



The control must be purchased as an accessory



Characteristics

2.20-9.00 kW | 7 power levels

New design

203 mm deep (2.20 kW) | Very compact design

29 dB(A) (2.20-2.80 kW) | Extremely quiet

Standard washable filter

Model		HKEU 225 XRV-P	HKEU 285 XRV-P	HKEU 365 XRV-P	HKEU 455 XRV-P	HKEU 565 XRV-P	HKEU 715 XRV-P	HKEU 905 XRV-P	
Control (included)	type	none							
Rated cooling capacity	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00	
Rated heating capacity	kW	2.40	3.20	4.00	5.00	6.30	8.00	10.00	
Electrical data									
Power	Ph-V-Hz	1-220~240V-50Hz							
Electrical absorption	W	28	30	40	45	55	82		
Product specifications									
Air flow (1)	Max~Min	m³/h	422~356	417~316	656~488	594~424	747~547	1195~809	1421~867
Sound pressure level at 1 m (1)	Max~Min	dB(A)	31~29	31~29	33~30	35~31	38~34	44~36	48~38
Sound power level (1)	Max~Min	dB(A)	46~44	46~44	48~45	50~46	53~49	59~51	63~53
Dimensions	LxHxD	mm	835x280x203			990x315x223		1194x343x262	
Net weight		Kg	8.4	9.5	11.4	12.8	17		
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")			9.52 (3/8") - 15.9 (5/8")			
Condensate drain		Ø mm	16						
Accessories									
Remote control		DHIR-5-6-XRV-K-P							
Wired remote control		DHW-5-6-XRV-K-P							
Optional parts									
Centralised control		See on page 123							

(1) Values related to Max and Min speed of 7 levels settable by remote control.

HSFU XRV-P Floor/ceiling



The control must be purchased as an accessory



Characteristics

5.60-14.00 kW | 5 power levels

Auto Swing function | Optimizes the distribution of air flow in the environment

Built-in electronic expansion valve

Easy installation with unit attached to the wall or ceiling

Model		HSFU 565 XRV-P	HSFU 715 XRV-P	HSFU 905 XRV-P	HSFU 1125 XRV-P	HSFU 1405 XRV-P
Control (included)	type	none				
Rated cooling capacity	kW	5.60	7.10	9.00	11.20	14.00
Rated heating capacity	kW	6.30	8.00	10.00	12.50	15.00
Electrical data						
Power	Ph-V-Hz	1-220~240V-50Hz				
Electrical absorption	W	115	115	130	180	180
Product specifications						
Air flow (1)	Max~Min	m³/h	930~720		1280~1050	1890~1580
Sound pressure level at 1 m (1)	Max~Min	dB(A)	43~38		45~40	47~42
Sound power level (1)	Max~Min	dB(A)	56~51		58~53	60~55
Dimensions	LxHxD	mm	990x660x203		1280x660x203	1670x680x244
Net weight		Kg	28		35	48
Refrigerant connections	Liquid/Gas	Ø mm (inch)	9.52 (3/8") - 15.9 (5/8")			
Condensate drain		Ø mm	16			
Accessories						
Remote control		DHIR-5-6-XRV-K-P				
Wired remote control		DHW-5-6-XRV-K-P				
Optional parts						
Centralised control		See on page 123				

(1) Values related to Max and Min speed of 7 levels settable by remote control.