

PROJECT VRF R410A FULL DC INVERTER

.....

HTFU XRV-P

8-ways compact cassette 60x60



The control must be purchased as an accessory



Ultra-compact design

22 dB(A) (2.20~2.80 kW) | Extremely quiet

360° air diffusion

Condensate drain pump with possibility of raising the discharge up to 500 mm from the lower height

Model			HTFU 225 XRV-P	HTFU 285 XRV-P	HTFU 365 XRV-P	HTFU 455 XRV-P
Rated capacity	Cooling	kW	2.20	2.80	3.60	4.50
	Heating	kW	2.40	3.20	4.00	5.00
Electrical data						
Power supply		Ph-V-Hz	1-220~240V-50Hz			
Electrical absorption		W	35	35	40	50
Product specifications						
External dimensions	LxHxD	mm	630x260x570			
Net weight		Kg	18		19.2	
Sound pressure level at 1.4 m ¹	Max~Min	dB(A)	35~22		41~28	
Sound power level ¹	Max~Min	dB(A)	51~38		56~43	
Air flow ¹	Max~Min	m³/h	576~405		604~400	
Refrigerant connections	Liquid/Gas	ø mm (inch)	6.35 (1/4") - 12.7 (1/2")			
	Condensate drain	ø mm	32			
Accessories						
Decorative panel			TFP 155 XRV-P			
Dimensions	LxHxD	mm	647x50x647			
Net weight		Kg	2.5			
Remote control			DHIR-5-6-XRV-K-P			
Wired remote control			DHW-5-6-XRV-P			
Optional parts						
Centralized control			DHC-8-64-XRV-P			

1. Values related to Max and Min speed of 7 levels settable by remote control.

HTBU XRV-P

8-ways cassette 84x84



The control must be purchased as an accessory



Optimised fan design to attenuate air resistance and reduce noise level

Condensate drain pump with possibility of raising the discharge up to 750 mm from the lower height

Pre-set for the connection of an outside air intake channel

Model			HTBU 565 XRV-P	HTBU 715 XRV-P	HTBU 905 XRV-P	HTBU 1125 XRV-P	HTBU 1405 XRV-P	
Rated capacity	Cooling	kW	5.60	7.10	9.00	11.20	14.00	
	Heating	kW	6.30	8.00	10.00	12.50	16.00	
Electrical data								
Power supply		Ph-V-Hz	1-220~240V-50Hz					
Electrical absorption		W	31	46	75	94		
Product specifications								
External dimensions		LxHxD	mm		840x230x840			840x300x840
Net weight			Kg	23.2		28.4	30.7	
Sound pressure level at 1.4 m ¹		Max~Min	dB(A)	43~34	45~34	47~36	50~38	
Sound power level ¹		Max~Min	dB(A)	56~47	58~47	61~50	64~52	
Air flow ¹		Max~Min	m ³ /h	1029~704	1200~748	1596~1034	1727~1224	
Refrigerant connections		Liquid/Gas	ø mm (inch)	9.52 (3/8") - 15.9 (5/8")				
		Condensate drain	ø mm	32				
Accessories								
Decorative panel			TBP 712 IHXR					
Dimensions		LxHxD	mm	950x70x950				
Net weight			Kg	5.8				
Remote control			DHIR-5-6-XRV-K-P					
Wired remote control			DHW-5-6-XRV-P					
Optional parts								
Centralized control			DHC-8-64-XRV-P					

1. Values related to Max and Min speed of 7 levels settable by remote control.