

PROJECT VRF R410A FULL DC INVERTER

.....

HTFU XRV-P

8-ways compact cassette 60x60



The control must be purchased as an accessory



Ultra-compact design

22 dB(A) (2.20~2.80 kW) | Extremely quiet

360° air diffusion

Condensate drain pump with possibility of raising the discharge up to 500 mm from the lower height

| Model | | | HTFU 225 XRV-P | HTFU 285 XRV-P | HTFU 365 XRV-P | HTFU 455 XRV-P |
|--|-------------------------|-------------------|---------------------------|----------------|----------------|----------------|
| Rated capacity | Cooling | kW | 2.20 | 2.80 | 3.60 | 4.50 |
| | Heating | kW | 2.40 | 3.20 | 4.00 | 5.00 |
| Electrical data | | | | | | |
| Power supply | | Ph-V-Hz | 1-220~240V-50Hz | | | |
| Electrical absorption | | W | 35 | 35 | 40 | 50 |
| Product specifications | | | | | | |
| External dimensions | | LxHxD | 630x260x570 | | | |
| Net weight | | Kg | 18 | | 19.2 | |
| Sound pressure level at 1.4 m ¹ | Max~Min | dB(A) | 35~22 | | 41~28 | |
| | Max~Min | dB(A) | 51~38 | | 56~43 | |
| Air flow ¹ | Max~Min | m ³ /h | 576~405 | | 604~400 | |
| | Refrigerant connections | Liquid/Gas | 6.35 (1/4") - 12.7 (1/2") | | | |
| | Condensate drain | ø mm | 32 | | | |
| Accessories | | | | | | |
| Decorative panel | | | TFP 155 XRV-P | | | |
| Dimensions | | LxHxD | 647x50x647 | | | |
| Net weight | | Kg | 2.5 | | | |
| Remote control | | | DHIR-5-6-XRV-K-P | | | |
| Wired remote control | | | DHW-5-6-XRV-P | | | |
| Optional parts | | | | | | |
| Centralized control | | | DHC-8-64-XRV-P | | | |

1. Values related to Max and Min speed of 7 levels settable by remote control.

HTBU XRV-P

8-ways cassette 84x84



The control must be purchased as an accessory



Optimised fan design to attenuate air resistance and reduce noise level

Condensate drain pump with possibility of raising the discharge up to 750 mm from the lower height

Pre-set for the connection of an outside air intake channel

| Model | | | HTBU 565 XRV-P | HTBU 715 XRV-P | HTBU 905 XRV-P | HTBU 1125 XRV-P | HTBU 1405 XRV-P |
|--|-------------------------|-------------------|---------------------------|----------------|----------------|-----------------|-----------------|
| Rated capacity | Cooling | kW | 5,60 | 7,10 | 9,00 | 11,20 | 14,00 |
| | Heating | kW | 6,30 | 8,00 | 10,00 | 12,50 | 16,00 |
| Electrical data | | | | | | | |
| Power supply | | Ph-V-Hz | 1-220~240V-50Hz | | | | |
| Electrical absorption | | W | 31 | 46 | 75 | 94 | |
| Product specifications | | | | | | | |
| External dimensions | | LxHxD | 840x230x840 | | | 840x300x840 | |
| Net weight | | Kg | 23,2 | | 28,4 | 30,7 | |
| Sound pressure level at 1.4 m ¹ | Max~Min | dB(A) | 43~34 | 45~34 | 47~36 | 50~38 | |
| | Max~Min | dB(A) | 56~47 | 58~47 | 61~50 | 64~52 | |
| Air flow ¹ | Max~Min | m ³ /h | 1029~704 | 1200~748 | 1596~1034 | | 1727~1224 |
| | Refrigerant connections | Liquid/Gas | 9,52 (3/8") - 15,9 (5/8") | | | | |
| | Condensate drain | ø mm | 32 | | | | |
| Accessories | | | | | | | |
| Decorative panel | | | TBP 712 IHXR | | | | |
| Dimensions | | LxHxD | 950x70x950 | | | | |
| Net weight | | Kg | 5,8 | | | | |
| Remote control | | | DHIR-5-6-XRV-K-P | | | | |
| Wired remote control | | | DHW-5-6-XRV-P | | | | |
| Optional parts | | | | | | | |
| Centralized control | | | DHC-8-64-XRV-P | | | | |

1. Values related to Max and Min speed of 7 levels settable by remote control.