

.....

MULTISPLIT INDOOR UNITS

Console HFIU 351-501 ZAL



Extremely compact with only **200 mm depth**

Possibility of **double delivery**, from upper and lower flap

Double installation option, floor or wall using a bracket
Remote control included as standard



| Model | | | HFIU 351 ZAL | HFIU 501 ZAL |
|----------------------------------------------|--------------|---------|--------------------------|--------------------------|
| Type | | | Console type indoor unit | |
| Control (included) | | | Remote control | |
| Rated capacity | Cooling | kW | 3.50 | 4.90 |
| | Heating | kW | 3.80 | 5.20 |
| Electrical data | | | | |
| Power supply | Outdoor unit | Ph-V-Hz | 1-220~240V-50Hz | |
| Connection wires between I.U. and O.U. | | no. | 4 | 4 |
| Refrigerant circuit | | | | |
| Diameter of refrigerant piping on liquid/gas | mm (inches) | | 6.35(1/4") / 9.52(3/8") | 6.35(1/4") / 12.74(1/2") |
| Product specifications | | | | |
| Dimensions | LxDxH | mm | 794x200x621 | 794x200x621 |
| Net weight | | Kg | 14.9 | 14.9 |
| Sound power level | Hi | dB(A) | 54 | 55 |
| Sound pressure level | Hi/Mi/Lo/ULo | dB(A) | 37/34/27 | 41/38/32 |
| Treated air volume | Hi/Mi/Lo | m³/h | 650/580/490 | 780/690/600 |
| Optional parts | | | | |
| Wi-Fi module | | | HKM-WiFi-TB | |
| Wired remote control | | | NO | |
| Manual centralized control | | | NO | |
| Wi-Fi centralized control | | | NO | |

MULTISPLIT INDOOR UNITS

Ceiling HSFU 531 ZAL



Double installation flexibility

Turbo function, for heating and cooling rooms quickly

Remote control included as standard



| Model | | | HSFU 531 ZAL |
|----------------------------------------------|--------------|---------|-----------------------------|
| Type | | | Ceiling type indoor unit |
| Control (included) | | | Remote control |
| Rated capacity | Cooling | kW | 5.30 |
| | Heating | kW | 5.60 |
| Electrical data | | | |
| Power supply | Outdoor unit | Ph-V-Hz | 1-220~240V-50Hz |
| Connection wires between I.U. and O.U. | | no. | 4 |
| Refrigerant circuit | | | |
| Diameter of refrigerant piping on liquid/gas | mm (inches) | | 6.35(1/4") / 12.74(1/2") |
| Product specifications | | | |
| Dimensions | LxDxH | mm | 1068x675x235 |
| Net weight | | Kg | 28 |
| Sound power level | Hi | dB(A) | 57 |
| Sound pressure level | Hi/Mi/Lo/ULo | dB(A) | 43.5/41/36.5/24 |
| Treated air volume | Hi/Mi/Lo | m³/h | 958/839/723 |
| Optional parts | | | |
| Wi-Fi module | | | On demand |
| Wired remote control | | | DHW-WT-ZA |
| Centralized control | | | DTC IHXR TOUCH / DTCWT IHXR |
| Wi-Fi centralized control | | | XRV Mobile BMS |