

.....

# MULTISPLIT INDOOR UNITS

Console HFIU 351-501 ZAL



Extremely compact with only **200 mm depth**

Possibility of **double delivery**, from upper and lower flap

Double installation option, floor or wall using a bracket

Remote control included as standard



Model	HFIU 351 ZAL		HFIU 501 ZAL	
Type	Console type indoor unit			
Control (included)	Remote control			
Rated capacity	Cooling	kW	3.50	4.90
	Heating	kW	3.80	5.20
<b>Electrical data</b>				
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz	
Connection wires between I.U. and O.U.	no.		4	4
<b>Refrigerant circuit</b>				
Diameter of refrigerant piping on liquid/gas	mm (inches)		6.35(1/4") / 9.52(3/8")	
<b>Product specifications</b>				
Dimensions	LxDxH	mm	794x200x621	
Net weight			14.9	
Sound power level	Hi	dB(A)	54	
Sound pressure level	Hi/Mi/Lo/ULo	dB(A)	37/34/27	
Treated air volume	Hi/Mi/Lo	m³/h	650/580/490	
<b>Optional parts</b>				
Wi-Fi module	HKM-WiFi-TB			
Wired remote control	NO			
Manual centralized control	NO			
Wi-Fi centralized control	NO			

# MULTISPLIT INDOOR UNITS

Ceiling HSFU 531 ZAL



Double installation flexibility

Turbo function, for heating and cooling rooms quickly

Remote control included as standard



Model	HSFU 531 ZAL			
Type	Ceiling type indoor unit			
Control (included)	Remote control			
Rated capacity	Cooling	kW	5.30	
	Heating	kW	5.60	
<b>Electrical data</b>				
Power supply	Outdoor unit	Ph-V-Hz	1-220~240V-50Hz	
Connection wires between I.U. and O.U.	no.		4	
<b>Refrigerant circuit</b>				
Diameter of refrigerant piping on liquid/gas	mm (inches)		6.35(1/4") / 12.74(1/2")	
<b>Product specifications</b>				
Dimensions	LxDxH	mm	1068x675x235	
Net weight			28	
Sound power level	Hi	dB(A)	57	
Sound pressure level	Hi/Mi/Lo/ULo	dB(A)	43.5/41/36.5/24	
Treated air volume	Hi/Mi/Lo	m³/h	958/839/723	
<b>Optional parts</b>				
Wi-Fi module	On demand			
Wired remote control	DHW-WT-ZA			
Centralized control	DTC IHXR TOUCH / DTCWT IHXR			
Wi-Fi centralized control	XRV Mobile BMS			