

# PROJECT VRF R410A

## XRV MULTI SYSTEM - FULL DC INVERTER

### HKEU XRV-K WALL



Remote control  
(standard)



8 power levels: 1.50~9.00 kW.

New design for models 7.10~9.00 kW.

Right side refrigerant connection (7.10~9.00 kW).

Extremely quiet: only 23 dB(A) (1.50 kW)

only 29 dB(A) (2.20 ~3.60 kW).

DC Inverter fan.

New built-in electronic expansion valve with 2000 pulse/min.

Washable standard filter & anti-formaldehyde filter to eliminate the harmful effects of the gas released in the environments.

Model		HKEU 155 XRV-K	HKEU 225 XRV-K	HKEU 285 XRV-K	HKEU 365 XRV-K	HKEU 455 XRV-K	HKEU 565 XRV-K	HKEU 715 XRV-K	HKEU 905 XRV-K						
Cooling capacity	kW	1.5	2.2	2.8	3.6	4.5	5.6	7.1	9.0						
Heating capacity	kW	1.7	2.6	3.2	4.0	5.0	6.3	8.0	10.0						
Dehumidifying capacity	l/h	0.5	0.7	1	1.2	1.5	1.8	2	2.2						
Power supply	Volt/Hz/Ph	220/50/1													
Electric consumpt.	W	15	19	22	26	31	50	67							
Air flow	Lo/Me/Hi	337/389/447		417/462/505		460/499/564		577/705/841		708/840/915		714/916/1211		710/915/1373	
Noise level at 1 m	Lo/Me/Hi	23/25/28		29/30/31		34/36/38		34/38/45		34/38/46					
Noise level at 2.5 m	Lo/Me/Hi	15/17/21		21/22/23		26/28/30		26/30/37		26/30/38					
Dimensions	LxHxD	mm		915x290x230		1070x315x230		1250x325x230							
Net weight	kg	11.6		12		14.4		18.3							
Refrigerant connections	Liquid	mm/inches		ø 6.35 (1/4")		ø 9.53 (3/8")		ø 15.9 (5/8")							
	Gas	mm/inches		ø 12.7 (1/2")		ø 15.9 (5/8")									
Condensate drain	ø mm	16.5													
Refrigerant control	Type	Built-in electronic expansion valve													
Remote control	Type	IR Remote Control (standard)													

### HSFU XRV-K FLOOR/CEILING



Remote control  
(standard)



5 power levels: 5.60~14.00 kW.

3 fan speeds.

The innovative Auto Swing & Wide Angle functions: the motorized horizontal & vertical louvres optimally adjust the air flow, guaranteeing better air distribution inside the air-conditioned room.

DC Inverter fan.

Waterproofing of the condensate drip tray (special treatment with water-repellent film)

Built-in electronic expansion valve.

Easy installation with unit attached to the wall or ceiling (brackets supplied standard).

Electric wiring and refrigerant connections can be reached from the air intake grille.

Model		HSFU 565 XRV-K	HSFU 715 XRV-K	HSFU 905 XRV-K	HSFU 1125 XRV-K	HSFU 1405 XRV-K	
Cooling capacity	kW	5.6	7.1	9.0	11.2	14.0	
Heating capacity	kW	6.3	8.0	10.0	12.5	15.5	
Dehumidifying capacity	l/h	1.9	2.4	3.0	3.8	4.0	
Power supply	Volt/Hz/Ph	220/50/1					
Electric consumpt.	W	94	126	130			
Air flow	Lo/Me/Hi	720/830/930		1050/1170/1280		1580/1700/1890	
Noise level at 1 m	Lo/Me/Hi	36/38/40		40/43/45		42/45/47	
Noise level at 2.5 m	Lo/Me/Hi	28/30/32		32/35/37		34/37/39	
Dimensions	LxHxD	990x660x203		1280x660x203		1670x680x244	
Net weight	kg	27		33		49	
Refrigerant connections	Liquid	mm/inches		ø 9.53 (3/8")		ø 15.9 (5/8")	
	Gas	mm/inches		ø 15.9 (5/8")			
Condensate drain	ø mm	25					
Refrigerant control	Type	Built-in electronic expansion valve					
Remote control	Type	IR Remote Control (standard)					