

## PROJECT VRF R410A FULL DC INVERTER

.....

# HKEU XRV-P Wall



Compact design  
Washable standard filter

**203 mm deep** (2.20~2.80 kW)  
extremely compact

**29 dB(A)** (2.20~2.80 kW)  
extremely silent

**The control must be  
purchased as an accessory**

| Model                                      |            |           | HKEU 225 XRV-P            | HKEU 285 XRV-P | HKEU 365 XRV-P | HKEU 455 XRV-P | HKEU 565 XRV-P            | HKEU 715 XRV-P | HKEU 905 XRV-P |
|--------------------------------------------|------------|-----------|---------------------------|----------------|----------------|----------------|---------------------------|----------------|----------------|
| Rated capacity                             | Cooling    | kW        | 2.20                      | 2.80           | 3.60           | 4.50           | 5.60                      | 7.10           | 9.00           |
|                                            | Heating    | kW        | 2.40                      | 3.20           | 4.00           | 5.00           | 6.30                      | 8.00           | 10.00          |
| Electrical data                            |            |           |                           |                |                |                |                           |                |                |
| Power supply                               |            | Ph-V-Hz   | 1-220~240V-50Hz           |                |                |                |                           |                |                |
| Absorbed power                             |            | W         | 28                        |                | 30             | 40             | 45                        | 55             | 82             |
| Product specifications                     |            |           |                           |                |                |                |                           |                |                |
| Dimensions                                 | LxHxD      | mm        | 835x280x203               |                |                | 990x315x223    |                           | 1194x343x262   |                |
| Net weight                                 |            | Kg        | 8.4                       | 9.5            | 11.4           | 12.8           |                           | 17             |                |
| Sound power level <sup>1</sup>             | Max~Min    | dB(A)     | 46~44                     | 46~44          | 48~45          | 50~46          | 53~49                     | 59~51          | 63~53          |
| Sound pressure level at 1.4 m <sup>1</sup> | Max~Min    | dB(A)     | 31~29                     | 31~29          | 33~30          | 35~31          | 38~34                     | 44~36          | 48~38          |
| Treated air volume <sup>1</sup>            | Max~Min    | m³/h      | 422~356                   | 417~316        | 656~488        | 594~424        | 747~547                   | 1195~809       | 1421~867       |
| Diameter of connections                    | Liquid/Gas | mm (inch) | 6.35 (1/4") / 12.7 (1/2") |                |                |                | 9.52 (3/8") / 15.9 (5/8") |                |                |
|                                            | Condensate | mm        | 16                        |                |                |                |                           |                |                |
| Accessories                                |            |           |                           |                |                |                |                           |                |                |
| Remote control                             |            |           | DHIR-5-6-XRV-K-P          |                |                |                |                           |                |                |
| Wired control                              |            |           | DHW-5-6-XRV-P             |                |                |                |                           |                |                |
| Optional parts                             |            |           |                           |                |                |                |                           |                |                |
| Centralized control                        |            |           | DHC-8-64-XRV-P            |                |                |                |                           |                |                |

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.

# HSFU XRV-P Floor/ceiling



**Auto Swing function** | Optimises the  
distribution of air flow in the room  
Built-in electronic expansion valve

Easy installation with unit  
mounted to the floor or  
to the ceiling

**The control must  
be purchased as an  
accessory**

| Model                                      |            |           | HSFU 365 XRV-P            | HSFU 455 XRV-P | HSFU 565 XRV-P            | HSFU 715 XRV-P | HSFU 905 XRV-P            | HSFU 1125 XRV-P | HSFU 1405 XRV-P |
|--------------------------------------------|------------|-----------|---------------------------|----------------|---------------------------|----------------|---------------------------|-----------------|-----------------|
| Rated capacity                             | Cooling    | kW        | 3.60                      | 4.50           | 5.60                      | 7.10           | 9.00                      | 11.20           | 14.00           |
|                                            | Heating    | kW        | 4.00                      | 5.00           | 6.30                      | 8.00           | 10.00                     | 12.50           | 15.00           |
| Electrical data                            |            |           |                           |                |                           |                |                           |                 |                 |
| Power supply                               |            | Ph-V-Hz   | 1-220~240V-50Hz           |                |                           |                |                           |                 |                 |
| Absorbed power                             |            | W         | 49                        | 115            |                           |                | 130                       | 180             | 180             |
| Product specifications                     |            |           |                           |                |                           |                |                           |                 |                 |
| Dimensions                                 | LxHxD      | mm        | 990x660x203               |                |                           |                | 1280x660x203              | 1670x680x244    |                 |
| Net weight                                 |            | Kg        | 27                        | 28             |                           |                | 35                        | 48              |                 |
| Sound power level <sup>1</sup>             | Max~Min    | dB(A)     | 53~49                     | 56~51          |                           |                | 58~53                     | 60~55           |                 |
| Sound pressure level at 1.4 m <sup>1</sup> | Max~Min    | dB(A)     | 40~36                     | 43~38          |                           |                | 45~40                     | 47~42           |                 |
| Treated air volume <sup>1</sup>            | Max~Min    | m³/h      | 550~420                   | 930~720        |                           |                | 1280~1050                 | 1890~1580       |                 |
| Diameter of connections                    | Liquid/Gas | mm (inch) | 6.35 (1/4") / 12.7 (1/2") |                | 9.52 (3/8") / 15.9 (5/8") |                | 9.52 (3/8") / 15.9 (5/8") |                 |                 |
|                                            | Condensate | mm        | 16                        |                |                           |                |                           |                 |                 |
| Accessories                                |            |           |                           |                |                           |                |                           |                 |                 |
| Remote control                             |            |           | DHIR-5-6-XRV-K-P          |                |                           |                |                           |                 |                 |
| Wired control                              |            |           | DHW-5-6-XRV-P             |                |                           |                |                           |                 |                 |
| Optional parts                             |            |           |                           |                |                           |                |                           |                 |                 |
| Centralized control                        |            |           | DHC-8-64-XRV-P            |                |                           |                |                           |                 |                 |

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.