

HOT WATER

HWMB5 1080-1100 J

Heat pump water heater
monobloc 80 and 100 liters series "Ducted kitchen"



Monobloc heat pump water heater,
designed to be installed inside the kitchen
column unit

R290 | Refrigerant gas

65° C | Water temperature
with compressor only

Anti-legionella cycle

Stainless steel tank

Titanium Anode

Removable upper body with horizontal extraction,
to facilitate maintenance and installation
operations in narrow spaces
ErP Ready

PERFORMANCE & INCENTIVES

Model	LOAD	ENERGY CLASS	COP According EN 16147	ECO BONUS*	BONUS CASA*	CONTTO TERMICO 2.0*
HWMB5 1080 J	80 L	A+	2.93	✓	✓	✓
HWMB5 1100 J	100 L	A+	3.03	✓	✓	✓

* For Italian market only.

Model			HWMB5 1080 J	HWMB5 1100 J
Tank volume	L		80	110
Nominal thermal power ¹	W		1000	1000
Nominal power consumption ¹	W		210	210
Nominal COP ¹	W/W		4,76	4,76
Nominal DHW production capacity ¹	L/h		20,00	20,00
COPDHW ²	W/W		2,93	3,03
Test cycle profile ²	-		M	M
Hot water volume at 40°C ²	L		114	140
Energy efficiency (η _{wh}) ³	%		123,1	128,6
Energy efficiency class ³	-		A+	A+
IP protection rating	-		IPX1	IPX1
Hot water temperature regulation range	°C		35~65	35~65
Maximum hot water temperature compressor only	°C		65	65
Electrical data	Power supply	Ph-V-Hz	1-220~240V-50Hz	
	Integrative electrical resistance	W	1500	1500
	Maximum current (including resistance)	A	8,30	8,30
Refrigerant circuit data	Refrigerant ⁴	Type (GWP)	R290 (0,02)	R290 (0,02)
	Quantity	g	140	140
	Compressor	type	Rotary ON/OFF	
Hydraulic data	Tank material	-	Stainless Steel 304	
	DHW connections	inches	G1/2" (DN15)	G1/2" (DN15)
	Solar coil connections	inches	-	-
	Maximum operating pressure	bar	10	10
Air ducts	Air flow rate (with ducts)	m³/h	280	280
	Fan's static pressure	Pa	60	60
	Internal diameter	mm	125	125
	Maximum length	m	8	8
Product specifications	Working range (compressor only)	°C	-5~+43	-5~+43
	Anode type		Titanium electrode	
	Sound power level	dB(A)	45	45
	Dimensions (D x H)	mm	ø520x1160	ø520x1368
Controls	Net weight	kg	48	48
	On-board machine control		Included	
	WiFi module		Integrated	

1. Conditions: intake air 20° C DB (15° C WB), water inlet 15° C / outlet 55° C. 2. Test according to EN16147; air 7° C, water inlet 10° C.

3. Directive 2009/125/EC - ERP EU No. 814/2013 (SGS-CSTC certification for all models). 4. Refrigerant leakage contributes to climate change. When released into the atmosphere, refrigerants with a lower global warming potential (GWP) contribute less to global warming than those with a higher GWP. This appliance contains a refrigerant with a GWP of 1430. If 1 kg of this refrigerant were released into the atmosphere, the impact on global warming would be 1430 times greater than 1 kg of CO₂, over a period of 100 years. Under no circumstances should the user attempt to intervene on the refrigerant circuit or disassemble the product. In case of need, always contact qualified personnel.

HEATING



HORIZONTALLY REMOVABLE UPPER HEAT PUMP BODY

Easier maintenance and less space required for installation.



COMFORT AT HOME

Designed to be installed in the kitchen, like a traditional boiler, the “Ducted Kitchen” series fits comfortably inside the kitchen column, with air expelled outside.

SAFETY

The titanium anode provides corrosion protection without the need for regular replacement like magnesium anode.

Anti-legionella system: the danger of legionella bacteria is averted thanks to periodic cycles that raise the temperature of the water inside the tank above 70° C.

INSTALLATION WARNINGS

1. It is mandatory to install a safety and non-return valve on the cold water inlet. Failure to do so may seriously damage the equipment. Use a valve with a 0.7 MPa setting. For the installation location, refer to the piping connection diagram.
2. The safety valve discharge pipe must be vertical and must not be placed in an environment at risk of freezing.
3. Water must be able to drip freely from the tube and its end must be left free.
4. The safety valve must be tested regularly to ensure it is working properly and to remove any limescale that may be blocking it.
5. Installation must be carried out in strict compliance with current regulations (R290).

HYDRAULIC CONNECTION DIAGRAM

