

# HKEU XRV-P

## Wall



Compact design  
Washable standard filter

**203 mm deep** (2.20-2.80 kW)  
extremely compact

**29 dB(A)** (2.20-2.80 kW)  
extremely silent

**The control must be purchased as an accessory**

Model			HKEU 225 XRV-P	HKEU 285 XRV-P	HKEU 365 XRV-P	HKEU 455 XRV-P	HKEU 565 XRV-P	HKEU 715 XRV-P	
Rated capacity	Cooling	kW	2.20	2.80	3.60	4.50	5.60	7.10	
	Heating	kW	2.40	3.20	4.00	5.00	6.30	8.00	
<b>Electrical data</b>									
Power supply		Ph-V-Hz	1-220~240V-50Hz						
Absorbed power		W	28		30	40	45	55	
<b>Product specifications</b>									
Dimensions		LxHxD	835x280x203			990x315x223		1194x343x262	
Net weight		Kg	8.4	9.5	11.4	12.8		17	
Sound power level <sup>1</sup>		Max~Min	dB(A) 46~44		48~45	50~46		53~49	
Sound pressure level at 1.4 m <sup>1</sup>		Max~Min	dB(A) 31~29		33~30	35~31		38~34	
Treated air volume <sup>1</sup>		Max~Min	m <sup>3</sup> /h 422~356		417~316	656~488		594~424	
Diameter of connections		Liquid/Gas	mm (inch) 6.35 (1/4") / 12.7 (1/2")			9.52 (3/8") / 15.9 (5/8")		9.52 (3/8") / 15.9 (5/8")	
		Condensate	mm 16						
<b>Accessories</b>									
Remote control			DHIR-5-6-XRV-K-P						
Wired control			DHW-5-6-XRV-P						

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.

# HSFU XRV-P

## Floor/ceiling



**Auto Swing function** | Optimises the distribution of air flow in the room

Built-in electronic expansion valve  
Easy installation with unit mounted to the floor or to the ceiling

**The control must be purchased as an accessory**

Model			HSFU 365 XRV-P	HSFU 455 XRV-P	HSFU 565 XRV-P	HSFU 715 XRV-P	HSFU 905 XRV-P	HSFU 1125 XRV-P	HSFU 1405 XRV-P
Rated capacity	Cooling	kW	3.60	4.50	5.60	7.10	9.00	11.20	14.00
	Heating	kW	4.00	5.00	6.30	8.00	10.00	12.50	15.00
<b>Electrical data</b>									
Power supply		Ph-V-Hz	1-220~240V-50Hz						
Absorbed power		W	49	115			130	180	180
<b>Product specifications</b>									
Dimensions		LxHxD	990x660x203			1280x660x203		1670x680x244	
Net weight		Kg	27	28			35	48	
Sound power level <sup>1</sup>		Max~Min	dB(A) 53~49		56~51		58~53		60~55
Sound pressure level at 1.4 m <sup>1</sup>		Max~Min	dB(A) 40~36		43~38		45~40		47~42
Treated air volume <sup>1</sup>		Max~Min	m <sup>3</sup> /h 550~420		930~720		1280~1050		1890~1580
Diameter of connections		Liquid/Gas	mm (inch) 6.35 (1/4") / 12.7 (1/2")			9.52 (3/8") / 15.9 (5/8")		9.52 (3/8") / 15.9 (5/8")	
		Condensate	mm 16						
<b>Accessories</b>									
Remote control			DHIR-5-6-XRV-K-P						
Wired control			DHW-5-6-XRV-P						

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.